

True Stile & Rail Steel Doors

| | |
|-------------------|--|
| Description | True Stile & Rail doors are built-to-order, suitable for both interior and exterior locations. |
| NAAMM / HMMA | 860 (Welded 3" OC, Filled Seamless) 861 (Continuous Weld, Seamless Edge) |
| SDI | II/1, III/1, IV/1 (Open Seam Edge) II/2, III/2 & 3, IV/2 (Seamless Edge) (per A250.8-2003, Level / Model) |
| Material | 1. Cold Rolled Steel 2. A60 or G90 Galvanized |
| Faces | 18, 16, 14 or 12 GA |
| Door Edges | 1-3/4" thick, beveled, 1/8" in 2" |
| Vertical Edges | Continuous Welded, Seamless See Vertical Door Edges |
| Top / Bottom | 16 GA Channels See Door Top & Bottoms |
| Reinforcements | Hinges: 7 GA, 1-1/2" X 10" Locks: 11 GA or equal # threads Closers: 14 or 12 GA |
| Core Options | Fiberglass, Urethane, Honeycomb, Styrene |
| Fire Rating | See Fire Rated |
| Bullet Resistant | See Bullet Resistant |
| STD Primer | Gray, EPA Approved, Alkyd, zinc compound primer, standard Finish paint also available See Finishes |
| Quick Ship | Contact Factory |

NOTE: Above door data varies depending on specific design criteria



Construction

- True Stile & Rail Construction
- Fully Welded - NO TIE RODS
- All Seams Continuously Welded and Finished Smooth

