





Sound Control Frames

Fire Rated Frame Options



SAMPLE ELEVATIONS

SIZE		FIRE RATING							MATERIALS + CONST				LIMITATIONS									
Max. Door Size (in.)	Single or Pair	Max. Overall Width	Max. Overall height	Max Panel Width	Max. Panel Height	20 Minute	3/4 Hour	1 Hour	1-1/2 Hour	3 Hour	16 Gauge	14 Gauge	12 Gauge	Welded	Stainless Steel	Seal-Tek™ Profile	Min. Throat Size	Max. Throat Size	Min. Face Width	Max. Face Width	Max Head Height	Max. Sill Height
51 X 120	S					■	■	■	■	■	■	■	■	■	■		2	13	1 1/8	6	6	
102 X 120	PR					■	■	■	■	■	■	■	■	■	■		2	13	1 1/8	6	6	

NOTE: Above frame data varies depending on specific design criteria

All Stiles Fire Rated assemblies are built-to-order to your exact specifications. For assistance with design, labeling requirements and multiple integrated features, contact factory.

For additional elevations, see [Sound Control](#)

Stiles®

Steel Door + Window Systems

© 2010 Stiles Custom Metal, Inc. 0710

Stiles Custom Metal Inc
1885 Kinser Road
Ceres CA USA 95307

T 209 / 538-3667
F 209 / 538-2776
www.stilesdoor.com